


Spe-ed SFE-4

4-Vessel Simultaneous Oven-based Extraction System

Designed for every day use in the research lab, the *Spe-ed* SFE-4 is easy to use, cost-effective, and durable. The *Spe-ed* SFE-4 has all the advantages of the *Spe-ed* SFE-2 while expanding parallel processing capabilities up to four extractor vessels. This system doubles the processing capability of the *Spe-ed* SFE-2.

The system features:

- Data Logging
- Touch-screen Panel
- New Software
- Monitor from Smart Phone
- temperatures to 240°C
- pressure up to 10,000 psi (690 BAR)
- pump flow rates up to 400mL/min
- independent control of flow rates to each vessel
- fully-adjustable, non-clogging, variable restrictors
- parallel processing capabilities of up to 4 vessels from 5mL to 1.0L
- collection into SPE cartridges or standard glassware
- in-line trapping capabilities
- modifier addition capability
- multiple flow path capability
- extract directly from liquid samples



Why Supercritical Fluids?

Supercritical Fluids Revolutionize Your Processes

No longer an exotic laboratory curiosity, but now a cost-effective tool to improve your process development.

No matter what your business...

Natural products

- Medicinals
- Biomass extractions
- Fragrances/essential oils

Pharmaceuticals/foods

- Natural products
- Enzymatic reactions
- Reaction cleanups
- Hydrogenations

Material Science

- Nanoparticles
- Aerogels
- Coatings
- Impregnations
- Metal Injection Molding (MIM)

Electronics

- IC Cleaning
- Resist developer
- Micro Electro-Mechanical Machines (MEM) cleaning

Textiles

- Dyeing
- Impregnations

Cleaning

- Critical cleaning machine parts
- ICs
- MEMs

Subcritical/Supercritical Water

Carbon dioxide is in its supercritical fluid state when both the temperature and pressure equal or exceed the critical point of 31°C and 73 atm (see diagram). In its supercritical state, CO₂ has both gas-like and liquid-like qualities, and it is this dual characteristic of supercritical fluids that provides the ideal conditions for extracting compounds with a high degree of recovery in a short period of time.

By controlling or regulating pressure and temperature, the density, or solvent strength, of supercritical fluids can be altered to simulate organic solvents ranging from chloroform to methylene chloride to hexane. This dissolving power can be applied to purify, extract, fractionate, infuse, and recrystallize a wide array of materials.

Because CO₂ is non-polar, a polar organic co-solvent (or modifier) can be added to the supercritical fluid for processing polar compounds. By controlling the level of pressure/temperature/modifier, supercritical CO₂ can dissolve a broad range of compounds, both polar and non-polar.

Supercritical Fluids can revolutionize your processes!

A Supercritical Fluid

- is fast and selective
- allows for reduced extraction and purification steps
- provides decreased processing time
- has reduced organic solvents
- gives higher yield with lower cost

